

Portable Air Condition

Amcor's range of portable air conditioners and air coolers, create a refreshing environment for the home, office and commercial premises to ensure everyone's comfort. Keeping cool makes our work more productive, our sleep more comfortable and provides a more pleasant atmosphere. Amcor has a stylish range of technologically advanced products for every application and budget.



AMC7000/10000/12000(E)

- ideal choice of sizes to suit most average size rooms
- a choice of 7,200 Btu/hr (2.1kW), 10,000 Btu/hr (2.9kW) and 12,000 Btu/hr (3.5kW)
- machines in one unit size
- 1-8 hour timer on electromechanical controls, 1-12 hour timer on electronic touch controls
- 2-speed turbo fan
- directional air discharge louvers
- easy-clean, washable filter and replaceable, odour-absorbent carbon filter
- extendable exhaust hose (up to 1.5 metres) with window / wall fitting kit
- optional remote electronic touch controls
- optional heat pump for economical heating



TAM10000/12000E

- Cools most average size rooms, lounge, bedroom, office, small conservatory
- 3 in 1 single unit portable air conditioner 10000 Btu/hr (2.9kW) cooling or 12000 Btu/hr (3.5kW) dehumidifies as it cools, removes up to 24 litres per day
- 2 speed fan for quick and quiet operation
- 8 hour timer on electromechanical controls
- 1-12 hour timer On/Off electronic touch controls
- directional air discharge louvers
- optional remote and electronic touch controls
- optional heat pump for economical heating



AIRLINE 2000/2000E

- Suitable for use in most average size rooms
- Complete air treatment center: 5,500 Btu/hr (1.6kW) cooling capacity dehumidifies as it cools, removes up to 10 litres/ day activated carbon filter and washable dust filters
- 2 speed turbo fan
- 2000 watt fan heater (optional)
- fragrance dispenser (optional)
- ergonomic design with integral handle
- two large integrated back wheels and front castors for ease of movement including stairs
- integral, removable 3.5L water tank to collect condensation
- directional louvers
- extendable hose (up to 1.5 metres) with window / wall fitting kit
- 1-8 hour off timer on electromechanical controls
- 1-12 hour on/off timer on electronic touch controls

Electromechanical Version		AMC7000	AMC10000	AMC12000
Electronic Version		AMC7000E	AMC10000E	AMC12000E
Cooling Capacity	Btu/Hr	7200	10000	12000
Cooling Capacity	kW	2.1	2.9	3.5
Thermostat Range	°C	18-32	18-32	18-32
Dehumidification - Max	L/Day	12	18	24
Fan Speeds		2	2	2
Air Flow (at High Speed)	m3/Hr	440	470	520
Power Supply-50Hz	V	220-240	220-240	220-240
Power consumption	W	530	830	850
Ampere	A	2.38	3.9	4.2
Refrigerant	R	407C	407C	407C
Dimensions Width (inner/outer)	mm	377	377	377
Height (inner/outer)	mm	750	750	750
Depth (inner/outer)	mm	400	400	400
Weight (inner/outer)	kg	27	29	31

*NB. Cooling capacities are measured at 230V/50Hz, RT27 °C RH60% "

ers

Optional Features:

- mechanical or electronic touch controls with temperature display and on/off timer
- infra red remote control on electronic models
- heat pump or 2kW fan heater
- colour options including metallic finish



AMC15000/AMC15000E

- Mobile, split air conditioner
- Powerful and quiet 14,000 Btu/hr (4.1kW) cooling capacity
- Easily fitted through a window or wall using fittings and bracket provided
- Self-sealing refrigerant pipe for DIY installation
- 3 metre long umbilical pipework
- 1-8 hour timer on electromechanical controls, 1-12 hour timer on electronic touch controls
- 2-speed turbo fan
- directional air discharge louvers
- easy-clean, washable filter and replaceable odour-absorbant carbon filter
- optional remote control electronic touch controls
- optional heat pump for economical heating



Complete fitting kit supplied - split units with quick fit connections for easy DIY fitting.

Other designs and colour options available



PANEL T



PANEL V



Colour options



Tiptronic, touch-control facia available across the wide range of Amcor air conditioners

Airline 2000 Airline 2000E	TAM10000 TAM10000E	TAM12000 TAM12000E	AMC15000 AMC15000E
5500	10000	12000	14000
1.6	2.9	3.5	4.1
18-32	18-32	18-32	18-32
10	26	31	30
2	2	2	2
280	490	470	550
220-240	220-240	220-240	220-240
720	890	1070	1180
3	4.2	4.9	5.4
407C	407C	407C	407C
345	500	500	377/420
722	750	750	750/460
325	400	400	400/250
22.5	31	32	30 + 11