

HD 6/12-4 C+

A compact, versatile cold water High-Pressure Cleaner.

The HD 6/12-4 C+ is a high quality, powerful & robust machine. This unit comes complete with a 4 pole, long life air cooled electric motor for high cleaning efficiency. Compact dimensions, lightweight construction and excellent mobility make cleaning operations simpler and faster. The 2 large wheels make this unit highly manoeuvrable and means it can be easily transported. Built to clean in long and tough operating conditions the easy press trigger with soft grip inlay ensures fatigue free operation by reducing operator effort. Ideal for fast and tough cleaning jobs on the farm, in the workshop or in car dealerships.

- Robust 4 pole electric motor guarantees a long service life.
- 3 piston axial pump with brass water inlet and cylinder head for long service life.
- Easy press trigger gun is ergonomically shaped to reduce operation fatigue.
- Automatic pressure controlled shutdown upon trigger release for low energy consumption.
- Adjustable aluminium push handle provides easy manoeuvrability.
- Integrated accessory storage on the back of the unit with additional cable fixing and nozzle bag.
- Comes complete with dirtblaster.



Technical data

HD 6/12-4 C+

Power supply	(~V/Hz)	1/240/50
Water flow rate	(l/h)	300-600
Pressure	(bar/MPa)	20-120 / 2-12
Max. water feed temp.	(°C)	60
Connected load	(kW)	2.8
Weight	(kg)	29.8
Dimensions (L x W x H)	(mm)	375 x 360 x 935
Order No.		1.150-152

Target Markets

- Agriculture
- Workshops
- Automotive
- Contract Cleaners
- Craft
- Hire/Fleet
- Construction

Standard Accessories

- 10m High-Pressure hose (ID 8)
- Easy press trigger gun with soft grip inlay
- 850mm stainless steel rotating spray lance
- Triple nozzle 0°/25°/40°
- Dirtblaster

Optional Accessories

- 10m High-Pressure extension hose (6.389-891)
- Coupling (for above hose) (4.403-002)
- 1550 mm Lance (4.760-365)
- Push-on washing brush (4.762-324)
- Rotary wash brush (4.762-284)
- FR 30 Hard surface cleaner (2.641-065)
- Nozzle kit (for above) (2.640-401)

