



NVDQ570-2

NVQ570-22

# NVQ570-22 NVDQ570-2

These were the first models designed and manufactured completely in Structofoam and they have proven themselves to be the complete answer to engineering integrity.

Structofoam is our unique material specification that has superb strength and impact resistance allowing machines to be truly rugged yet without a weight penalty.

Power and performance are to the full Twinflo' standard with a choice of one or two-motored specifications. All models are equipped with dual 2-stage primary filter systems as standard, to which can be added giant Microflo' dust bags if required.

The rugged Structofoam container is mounted on 4 x 75mm (3") non-marking, heavy-duty castors and the compact size makes it ideal for numerous trades where it must frequently be moved from place to place such as builders, shop fitters, contractors etc.

The accessory kit is full 38mm (1 1/2") with stainless steel tube sets and even the 400mm (16") floor nozzle is a Structofoam design.

*For a middle range machine size, the specification, performance and convenience of the 570's would be difficult to beat.*

Model	Motor	Power	Airflow	Suction	Cap	Range	Weight	Dimensions
NVQ	1200W	230V	45 L/sec	2600mm	23L	26.8m	13.8Kgs	415 x 415
NVDQ	2400W	AC 50/60Hz	90 L/sec	2600mm	23L	26.8m	16.0Kgs	x 645mm

Also available 115V/120V specification.