

B&G FOGGERS

2400 Fogger



- 6 litre low profile tank
- One piece, seamless heavy duty copolymer tank
- Simple operation/filling/emptying/cleaning
- Corrosion Resistant
- Two stage fan motor (In Models 2400 & 2600)
- CE approved unit

Technical Data

Model	Max. Output (ml per minute)	Valve Setting	Output (ml per minute)	Mean Volume Diameter (microns)
2300	Fixed 270	N/A	270	
2400	Variable 0 - 270	¼ Turn	2.66	15
		½ Turn	5.32	21
		¾ Turn	16.27	32
		1 Turn	44.37	49
		Fully Open (approx 3 Turns)	270.00	
2600	Variable 0 – 540	¼ Turn	9.76	16
		½ Turn	22.19	21
		¾ Turn	35.5	22
		1 Turn	73.96	30
		Fully Open (approx 3 Turns)	540.00	

2600 Flex-A-Lite



- Fitted with either an 18inch or 4 foot flexible hose
- Adjustable flow control allowing users to accurately control the quantity and direction of the output
- The flow control provides adjustment of the chemical discharge from Ultra Low Volume (ULV) to a mist with flow rates between 0-540 ml/minute
- Strong and stable six-litre tank, made of a one-piece seamless heavy-duty copolymer
- 3 ½ inch tank opening for easy filling, emptying and cleaning
- All foggers are available in 240V or 110V