

# Diamond Grip Tape - Hazard

Diamond Grip - Hazard is an extremely tough, durable self-adhesive anti-slip tape with hazard chevrons for added protection for medium to high traffic areas. Along with possessing exceptional grip levels, the safety-grip is waterproof, can sustain most chemicals and, be used inside or out for added protection on steps or walkways.

## Features

- ◆ **Typical applications:** Perfect for industrial and construction sites, commercial premises, universities, public buildings, residential, retail, sports facilities and offices.
- ◆ **Material:** Aluminium Oxide (80 grit) with solvent acrylic adhesive.
- ◆ **Cleaning:** Dirt and debris can easily be removed using a stiff brush. Where dirt has become embedded, or to remove spillages, we recommend using a detergent and warm water.
- ◆ **Sustainability:** REACH compliant.
- ◆ **Warranty:** Lifetime.



Suitable for  
indoor and outdoor use



For more information about this product or, to place an order [click here](#)

Code	Metric	Imperial	Thickness	Weight	Type	Colour
DGHZ01BY	25mm x 18.3m	1" x 60'	0.8mm	0.4kg	Roll	Black/Yellow
DGHZ02BY	50mm x 18.3m	2" x 60'	0.8mm	0.7kg	Roll	Black/Yellow
DGHZ04BY	100mm x 18.3m	4" x 60'	0.8mm	1.4kg	Roll	Black/Yellow
DGHZ06BY	150mm x 18.3m	6" x 60'	0.8mm	2kg	Roll	Black/Yellow
DGHZ624BY	610mm x 150mm	2' x 6"	0.8mm	0.08kg	Cleat	Black/Yellow

Please note, the thickness can be +/- 0.2mm

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

# Diamond Grip Tape - Hazard

## Technical Specification

Slip resistant:	Exceptional slip resistance to level 3
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall
Water absorbent:	Great water absorbency to level 2
Crush resistant:	Great crush resistance to level 2
Adhesion:	5.5kg / 25mm
Application temperature:	10°C - 50°C
Chemical resistant:	Yes, resistant to most chemicals, grease and oils
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users
Dry area:	Yes
Wet area:	Yes
Wheeled area:	Due to the heavy-duty design, the tape can be crossed by trolleys and light weight machinery
Environment:	Suitable for indoor and outdoor use
Product testing:	<ul style="list-style-type: none"> <li>◆ Slip resistant tested to DIN 51130: 2014 - class R13</li> <li>◆ Tensile strength: 12kgF / 25mm</li> <li>◆ Elongation: 5%</li> </ul>
Sustainability:	REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)
Temperature resistance:	-30°C to +70°C
UV resistant:	Yes
Cleaning:	Dirt and debris can easily be removed using a stiff brush. Where dirt has become embedded, or to remove spillages, we recommend using a detergent and warm water