


ESD Kumfi Pebble

ESD Kumfi Pebble has been specially designed to dissipate static electricity and reduce fatigue for medium duty areas. Simple tasks - working, walking or, even sitting on certain types of stools, can create static electric. When left unchecked, static can discharge into static sensitive equipment, potentially causing damage. Our ESD Kumfi Pebble drains static from workers, preventing unpleasant static shocks, whilst also safeguarding equipment. The pebble surface design provides good anti-slip protection and the bevelled edges on all sides minimises the risk of tripping.

Optional accessories available - Common Grounding Point Cord - Socket, Coiled Earth Lead – 10mm to 10mm Stud, Wrist Band, Earth Bonding Plug, and Heel Grounder. The matting can be supplied with studs if required.

Features

- ▼ Typical applications: Ideal for assembly lines, logistics warehouses, individual work stations, around machinery, computer rooms, hospitals and the aerospace industry.
- Material: Microcellular vinyl.
- Cleaning: Wash with cold water and a mild detergent. The use of harsh detergents is not recommended.
- Sustainability: Recyclable material. REACH and RoHS compliant.
- Warranty: Lifetime.





For more information about this product or, to place an order click here

Code	Metric	Imperial	Thickness	Weight	Туре	Colour
EP2436BL	60cm x 91cm	2' x 3'	9.4mm	1.8kg	Mat	Black
EP2436BY	60cm x 91cm	2' x 3'	9.4mm	1.8kg	Mat	Black/Yellow
EP3660BL	91cm x 150cm	3' x 5'	9.4mm	4.1kg	Mat	Black
EP3660BY	91cm x 150cm	3' x 5'	9.4mm	4.1kg	Mat	Black/Yellow
EP360BL	91cm x 18.3m	3' x 60'	9.4mm	44kg	Roll	Black
EP360BY	91cm x 18.3m	3' x 60'	9.4mm	44kg	Roll	Black/Yellow



ESD Kumfi Pebble

Code	Metric	Imperial	Thickness	Weight	Type	Colour
EP36BL	91cm wide	3' wide	9.4mm	2.8kg	Cut length - per m	Black
EP36BY	91cm wide	3' wide	9.4mm	2.8kg	Cut length - per m	Black/Yellow
EA0522	Common Grounding Point Cord - Socket				Blue	
EA0531	Coiled Earth Lead – 10mm to 10mm Stud			Blue		
EA0542	Wrist Band			Blue		
EA0551	Earth Bonding Plug			Yellow		
EA0561	Heel Grounder				Blue/Black	

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number Please note, the width and length can be +/- 2%

Technical Specification					
Slip resistant:	Good slip resistance to level 1				
Anti-fatigue:	Great anti-fatigue properties, resistant to level 2				
Wear resistant:	Good wear resistant to level 1, suitable for low to medium footfall				
Cut to length:	Yes, mat can be cut to length				
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users				
Dry area:	Yes				
Environment:	Suitable for indoor use				
Flame retardant:	Yes				
Non-static (ESD):	Yes				
Product testing:	 Elongation 125% IEC61340-4-1 (category DIF), measured resistance: ESD Rg - Rg 10⁶ - 10⁹ ESD Rp - Rp 10⁶ - 10⁹ Fire rating US Pass Coefficient Friction Dry 0.79 Surface Flammability Pass 				



ESD Kumfi Pebble

Technical Specification

Sustainability:

- Recyclable material
- REACH (Registration, Evaluation, Authorization and Restrictions of Chemicals)
- RoHS (Restriction of Hazardous Substances)

Cleaning:

Wash with cold water with a mild detergent. The use of harsh detergents is not recommended

ESD Accessories



Common Grounding Point Cord - Socket



Coiled Earth Lead – 10mm to 10mm Stud



Wrist Band



Earth Bonding Plug



Heel Grounder