

Gum Removal

The GR4500 is a commercial chewing gum removal system incorporating an (up to) 4.5 bar pressure steam boiler with an integral chemical delivery system. Made from highly durable stainless steel construction the unit features a continuous fill boiler system allowing refill at any time during operation. This machine is ideally suited for smaller areas of chewing gum removal i.e. shopping centres, sports stadiums and local authority concerns.






© GR4500 Technical Specification

GR4500 Specification

Dimensions		Other	
Height [cm]	46	Supply voltage [V]	240
Height with handle [cm]	-	Cord length [m]	10
Depth [cm]	42		
Depth with handle and basket [cm]	-	Indicators	
Width [cm]	32	Steam pressure (boiler)	no
Weight [kg]	14	Steam Temperature (boiler)	digital
		Boiler ON	indication LED
Functions		Steam ready	indication LED
Steam [bar]	4.5	Refill watter	indication LED & beeper
Detergent	yes	Vacuum ON	no
Vacuum	no	Refill detergent	no
Capacities [litres]		Controls	
Water tank	5	Main switch	on machine body
Detergent tank	2.5	Mode switch	no
Vacuum tank	no	Steam trigger	on hose handle
Boiler	1.8	Detergent trigger	on hose handle
		Vacuum trigger	no
Wattage		Steam regulator	manual valve
Vacuum motor [W]	no	Detergent regulator	no
Boiler [W]	1950		
Nominal input power [W]	2000		



Accessories Included

• 4m steam only hose

- 2 x extension tubes
- Floor brush
- Triangular brush
- Large brush elbow

- Window squeegee
- Long nozzle
- Curved nozzle
- Detail brush nozzle
- 5 x round nylon brushes
- 5 x round brass brushes
- 55mm round brush