



### HD 13/35 Ge Cage

This product uses up to 350 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.







- 1 Industrial spray gun
- Robust and durable: The new Kärcher industrial trigger gun was designed specially for heavy-duty use.
- 2 Speed regulation
- The speed is automatically reduced in standby mode. This protects the engine and saves energy.
- 4 Independence

3 Mobility

### **TECHNICAL DATA AND EQUIPMENT**





#### HD 13/35 Ge Cage

- Robust industrial gun
- Dry run protection (optional)
- Speed regulation

Technical data		
Order no.		1.367-505.0
EAN code		4039784731004
Working pressure	bar / MPa	100-350 / 10-35
Flow rate	l/h	500-1300
Max. inlet temperature °C		max. 60
Pump type		Maximum performance Kärcher crankshaft pump
Drive		Honda GX 660 Petrol
Motor rating	kW	16
Weight	kg	135
Dimensions (L × W × H)	mm	930 × 800 × 920

Equipment		
Electro start		
High-pressure hose	m	10 / Heavy duty
Spray gun		Industrial trigger gun
Stainless steel lance	mm	700
Flat jet nozzle		I
Safety valve		I
Elapsed time counter		ī

■ Included in the scope of supply.

# HD 13/35 GE CAGE 1.367-505.0



























		01	1		B	Baraniakian	
		Order no.	Length		Price	Description	
High-pressure hoses							
Pressure hose	1	6.391-846.0				650 bar, M 22 x 1.5	
	2	6.391-856.0				650 bar, M 22 x 1.5.	
	3	6.391-848.0				650 bar, M 22 x 1.5	
	4	6.391-857.0				650 bar, M 22 x 1.5.	
	5	6.391-847.0					
	6	6.391-019.0				Durable, abrasion-resistant and flexible multi-layer steel-re	
						inforced hose with connection size M 22 × 1.5. Suitable for	
<b>-</b>						up to 620 bar working pressure.	_
Trigger guns		1, ==== 00.40	1			Leen the second second	
Kärcher industry gun	7	4.775-824.0				650 bar – industrial spray gun with optimised flow. Robust- ness and durability for professional use. Food-safe and	
						saltwater-resistant materials. Connector for HP hoses M 22	
						x 1.5.	
Spray lances		,			'		
Spray lance	8	4.760-679.0				With nozzle holder.	
	9	4.760-653.0					
	10	4.760-675.0					
	11	4.760-677.0				_	
Spray lance extension	12	4.760-699.0				Spray lance extension 800 mm, 65 MPa.	Ī
Power nozzles			1	·			
Flat jet nozzle	13	5.765-165.0				15° flat jet nozzle 15046 for high-pressure cleaner HD	I
	10					13/35. Suitable for working pressures of up to 350 bar and	
						1,300 l/h (petrol, 60 Hz).	
Point jet nozzle	14	5.765-161.0				Point jet nozzle 0046 for high-pressure cleaner HD 13/35.	
						Suitable for working pressures of up to 350 bar and 1,300	
BAKE allows and lolds						I/h (petrol, 60 Hz).	
Attachment kits	۱	1				le	П
Attachment kit water shortage	15	2.641-923.0				For petrol engines.	
protection ABS protection against water	16	2.851-028.0	+			ABS steering rollers.	+
shortage	10	2.031-020.0				ABS Steering rollers.	
Kupplungen und Verbinder		'	<u>'</u>				
Coupling	17	4.403-004.0				For connecting and extending HP hoses. Connection 2 × M2	2l _
						× 1.5. Brass with rubber protection.	<u>ا</u> [
Grease for stainless steel threaded	18	6.280-180.0				Grease for stainless steel screw connections.	
joints							Ľ
Single-jet rotary nozzles							
Rotary jet	19	4.767-173.0				350 bar, 1.35 mm, 1,300 l/h, M 20 × 1, brass.	
Power rotary jet F7	20	6.415-914.0				350 bar, 1.35 mm, 1,300 l/h, M 20 × 1, stainless steel.	
Power rotary jet repair kit F7	21	6.025-436.0				Repair kit for power rotary jet, order no. 6.415-914.0. Suita	
						ble for 350 bar working pressure and 1,300 l/h water flow	
Tool for shanging anti-		6.025.222.6	+			rate. Includes rotor, seat and 0-ring (28 × 2).	-
Tool for changing rotor seat	22	6.025-233.0				For F3, F4, F1, F25.	
Screw nozzles F21	00	L C 025 227 C				E24 severy on dispersy namely Critical Later woulder	
Dummy nozzle F21	23	6.025-237.0				F21 screw-on dummy nozzle. Suitable for working pressure of up to 3,000 bar.	S
Round jet nozzle F21, Saphir	24	9.886-216.0				Screw-on F21 sapphire round jet nozzle with a diameter of	+
		1.555 215.5				0.90 mm. Suitable for working pressures of up to 3,000 bar	- 1 1

<sup>■</sup> Included in the scope of supply. 

Available accessories.

# HD 13/35 GE CAGE 1.367-505.0

















MISSING PICTURE:
M:\print\9899828\_
std\_1\_86584\_acc.
tif

44

		Order no.	Length	Price	Description	
Pipe cleaning		1	1	 '		
Foot valve for pipe cleaning	25	6.470-223.0			Foot valve for convenient and safe use of accessories for effective pipe cleaning.	
Pipe cleaning nozzle, standard	26	5.763-090.0			Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	
Pipe cleaning nozzle, Quattro	27	5.763-091.0			For pipe cleaning hoses with G1/4" threaded connection: Quattro pipe cleaning nozzle. Nozzle configuration: 3x back ward and 1x forward.	:- E
Pipe cleaning nozzle, Rotor	28	5.763-092.0			For pipe cleaning hoses with G1/4" threaded connection: Rotor pipe cleaning nozzle. Nozzle configuration: 3x backward.	
Pipe cleaning hose	29	6.392-401.0			Flexible pressure hose (DN 8) for thorough pipe cleaning. 1 m long. Threaded connection for G1/4" nozzle.	0 [
	30	6.392-402.0			Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	Г
	31	6.392-403.0			For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	e [
Surface cleaner		1				
Surface Cleaner FRI 50 Me	32	2.643-577.0			Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steer ing rollers. Specific nozzle kits must be ordered separately.	-
Nozzle package 025 FRI 50 Me	33	6.415-045.0			Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzl size: 025.	e _
Abrasive blaster						
Required adapter for abrasive blasters	34	5.401-325.0			M 20 x 1 IG to 9/16" UNF AG.	
Abrasive blaster, incl. 3 x 0.7 nozzle	35	9.872-435.0			Abrasive spray head with nozzle size $3\times0.7$ mm for wet sand blasting. Only includes spray head. Without hose and lance.	
Replacement nozzle for abrasive blaster	36	6.025-346.0			Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	
F98 nozzle kit, D 0.70 mm	37	9.886-551.0			For wet sand blasting: three-nozzle kit for abrasive spray head. Nozzle size 0.7 mm.	
F98 nozzle for abrasive blaster	38	6.025-255.0			Nozzle (nozzle size 0.7 mm) for abrasive spray head for we sand blasting.	et [
Suction lance	39	6.025-258.0			For the suction of spray agents.	
Abrasive material hose	40	6.025-308.0			Abrasive hose.	
Mounting tool for nozzle set	41	6.025-257.0			For F98 nozzles.	
Abrasive	42	6.025-309.0			25 kg, 0.5-1.00 mm, garnet sand.	
	43	6.025-310.0			25 kg, 0.7-1.40 mm, garnet sand.	
Multi-jet rotary nozzles						
Nozzle carrier head TD09	44	9.899-828.0			6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	

<sup>■</sup> Included in the scope of supply. 

□ Available accessories.