



HD 728 B Cage

Cold water pressure washer with Honda 5.5hp petrol engine for use where no electrical connection is available. With protective tubular steel frame.










1 For the toughest jobs

- Sturdy tubular steel frame protects all components.
- Crane attachment point for use in the hire business, construction, agriculture and forestry.

TECHNICAL DATA AND EQUIPMENT.





HD 728 B Cage

- Robust, powder-coated tubular frame
- Portable
- Stainless steel spray lance

Technical data		
Order Number		1.187-908.0
EAN code		4054278297750
Operating pressure	bar / MPa	150 / 15
Max. pressure	bar / mbar	160 / 16
Flow rate	l/h	650
Max. water feed temperature	°C	60
Engine type		GX 160/Petrol
Engine manufacturer		Honda
Power rating	kW / hp	4 / 5,5
Weight	kg	35,5
Dimensions (L x W x H)	mm	570 × 434 × 430

Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	10
Spray lance	mm	600
Triple nozzle (0°/25°/40°)		Manual
Cage frame		
Anti-twist system (AVS)		-
Electric starter		-
Enclosed tubular frame with attachment point for handling by crane		
Quick Connect Kärcher standard nozzles		-
Servo Control		-
Vario-power spray lance		-
■ In abody d in abdition on a		

 \blacksquare Included in delivery.























				1			T	_
		Order Number	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides	5	1						
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	•
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	A
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	A
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m			A
Hose assembly premium DN12 21MPa 15m	8	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l h. With union on both sides. 2x M 22 x 1.5 with anti-kink	/
Hose assembly premium DN12 21MPa 40m	9	6.110-060.0	ID 12	210 bar	40 m		protection.	•
Hose assembly TR DN10 22MPa 10m	10	6.110-041.0	ID 10	220 bar	10 m			•
High-pressure hose, 10 m DN 6,	11	6.110-034.0	ID 6	250 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection.	_
AVS trigger gun connector	12	6.110-035.0	ID 6	250 bar	10 m		With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.)-
Longlife 400 with unions on both s		1		1			,	
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling	13	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	•
High-pressure hose Longlife 400, 20 m, DN 8, extension	14	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	4
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	15	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	•
High-pressure hose 1.5 m, DN 8, including connectors	16	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	
Longlife 400 high-pressure hose, 1 x EASY!Lock, 1 x M22 x 1.5, DN 8, 400 bar, 1.5 m	17	6.110-069.0	ID 8	400 bar	1,5 m		High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection.	
High-pressure hose packaged	18	6.110-038.0	ID 8	400 bar	10 m		Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANT!!Twist. Approved for 400 bar pressure.	
Longlife food industry version with	1	ı						
High pressure hose food DN 8 / 10 m	19	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5	•















		Order Number	Flow rate		Price	Description
Trigger guns						
EASY!Force Advanced	1	4.118-005.0				Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
Conversion kit 1 from high pressure hose	2	4.111-050.0				A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.
Conversion kit 2 from device	3	4.111-051.0				Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose.
Conversion kit 3 only EASY!Force	4	4.111-052.0				A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.
Quick connect						
Quick-fitting pipe union coupler trapezo	5	2.115-000.0				For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray [lance interface. With M 22 x 1.5 internal thread.
Quick-fitting pipe union plug nipp- le tra	6	2.115-001.0				Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread.

[■] Included in delivery.

Available accessories.

Extension hose.































		Order Number	Max. working pressure	Length			Price	Description	
Rotating spray lances									
Rotatable lance, 600 mm, ergonomic	1	4.112-007.0	300 bar	600 mm				600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.)-
Nozzle Light	2	2.680-002.0		125 mm				LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.	
Lance 250 mm, non-rotatable	3	4.112-027.0	300 bar	250 mm				600 mm stainless steel lance (manual coupling) with ergono)- 🔲
550 mm lance, non-rotatable	4	4.112-024.0	300 bar	400 mm				mic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 850 mm, rotatable, ergonomic	5	4.112-006.0	300 bar	840 mm				850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.)-
1050 mm lance, rotatable, ergonomic	6	4.112-000.0	300 bar	1050 mm				1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Lance 1550 mm, rotatable, ergonomic	7	4.112-018.0	300 bar	1550 mm				1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Lance 2050 mm, rotatable, ergonomic	8	4.112-021.0	300 bar	2050 mm				2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Jet pipe extension TR 1000 mm	9	4.112-048.0	300 bar	1000 mm				Spray lance extension with EASY!Lock connection. Length 1000 mm.	
Double lance			1						
Double lance 960 mm	10	2.112-016.0	310 bar	960 mm				960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance			1						
WC and gutter lance	11	4.112-029.0						Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				1	ı				
Flexible lance 1050 mm	12	4.112-035.0	210 bar	1050 mm				1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Articulated joint TR 20	13	4.112-057.0	300 bar					For hard-to-reach areas: High-pressure articulated joint wit infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Telescopic spray lance									
Telescopic jet pipe	14	4.112-037.0	225 bar	5400 mm				Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connection with rotary coupling. Connection for M 18 x 1.5 nozzle	- 🗆
Restraint belt for telescopic jet pipe	15	6.373-987.0						Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.	
Gutter cleaner			1						
Gutter cleaning lance	16	2.112-015.0		960 mm				The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance			ı		ı	1			
Underbody lance	17	4.112-032.0		700 mm				Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	





		Order Number	Max. working pressure	Length		Price	Description	
Additional handle	<u> </u>							H
Additional handle for EASY!Lock spray lances	18	4.321-380.0					Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	ַ

[■] Included in delivery.

Available accessories.

Extension hose.





		1	1	1			
		Order Number	Nozzle size			Price	Description
Power nozzle spray angle 25°							
Power nozzle spray angle 25°	1	2.113-006.0	38				Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °0	2	2.113-001.0	40				High-pressure nozzle with powerful jet for extremely stubborn dirt. $\hfill\Box$
Power nozzle spray angle 15°							
Power nozzle 15° - 038	3	2.113-044.0	38				Flat jet nozzle for stubborn dirt.
Power nozzle spray angle 40°							
Power nozzle spray angle 40°	4	2.113-003.0	40				Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

[■] Included in delivery.

Available accessories.

Extension hose.









Pint Planter and I		Order Number	Max. working pressure	Nozzle size		Price	Description
Dirt Blaster, small				ĺ			
Dirt blaster, small 040	1	4.114-020.0	180 bar	40			With rotating point jet for more efficient removal: the new performance dirt blaster with nozzle size 040 achieves up to 50% higher cleaning and area performance than its predecessor.
Dirt blaster, large							
Dirt blaster 04	2	4.114-041.0	300 bar	40			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.
Triple nozzles							
Triple nozzle 038	3	4.117-032.0	300 bar	38			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.

[■] Included in delivery.

Available accessories.

Extension hose.































		Order Number			Price	Description	
Nozzle union							
Nozzle screws	1	4.112-011.0				Nozzle screws with protectors for high-pressure and power	\mathbb{T}_{n}
IID determent injector						nozzles	
HP detergent injector Detergent injector for high and	2	4.637-032.0		ı	1	Detergent injector for independent high and low pressure	
low pressure (without nozzles)	2	4.037-032.0				dosage. Maximum dosage about 15%.	
Detergent injector for high pressu-	3	4.637-033.0				Cleaning agent dosage at high pressure 3 - 5 %	
re Machine-specific nozzle kit with on	dor no	2 627-170					工
Nozzle insert trapezoidal thread	4	4.769-005.0		I	I	For HD 500 - 700 l/h. Consists of nozzle insert + HP power	T
HD-GER.	4	4.709-003.0				nozzle + union	
Machine-specific nozzle kit with	5	4.769-045.0					_
order no. 3.637-170.0 HD 500- 700 l/h							
Nozzle insert with order no. 3.637-	001					1	
Nozzle insert for Order No. 3.637-	6	4.769-003.0				Nozzle insert for detergent injector 3.637-001 for high-	Т
001, high-pressure for machines up to 1100 l/h.						pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to	7	4.769-001.0				For low pressure with machines up to 1.100 l/h	+
1100 l/h		65 661.6				To low pressore warmacrimes op to 11100 yr	
Rotary coupling							
Rotary coupling	8	4.111-021.0				Kärcher rotary coupling prevents twisting and kinking of	
						high-pressure hoses for ease of use. Connector M 22 x 1.5	
Coupling						m. With grip protection.	\perp
Coupler -2xM22x1,5	9	4.111-037.0				Brass double connector for connecting and extending high-	Т
						pressure hoses. With rubber protection. Connector: 2x M 22	
Connector						x 1.5 m.	4
Nozzle connector/screw connector	10	4.111-022.0				Nozzle connector/screw connector for connecting high-	Т
NOZZIE COMMECTON/SCIEW COMMECTON	10	4.111 022.0				pressure nozzles and accessories to the high-pressure trig-	
						ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5	
						and 1x M 18 x 1.5.	+
Y distributor	11	4.111-024.0				Offers the option to connect two spray units to the machine installation on the high pressure outlet.	e. 🗆
Short spray unit	12	4.111-038.0				For attaching high-pressure nozzles and accessory parts to	Т
						HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	
Adapter EASY!Lock						THE HOZZIES.	
Adapter 1 M22AG-TR22AG	13	4.111-029.0				Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	14	4.111-030.0				Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	15	4.111-031.0				Adapter 3 to connect the old gun with the new spray lance	\pm
,	13					and new servo regulator	
Adapter M22 - Swivel	16	4.111-032.0				M22 x 1,5female and swivel connection. For extension of	
						high-pressure hoses with AVS connection or for usage of the	e 🗆
						telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	17	4.111-033.0				Adapter 5 to connect the new gun with the old spray lance	
Adaptor 6 TB22IC M22AC	1.0	4 111 024 0		-		and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	18	4.111-034.0				Adapter 6 to connect the new device with the old hose and the old hose with the new gun	









		Order Number		Price	Description	
Adapter 7 M18IG-TR20AG	19	4.111-035.0			Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	20	4.111-036.0			Adapter 8 to connect the new spray lance with the old nozzle	
ADAPTER for replacement TR22IG- M22AG Er	21	4.111-046.0			Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	

[■] Included in delivery.

Available accessories.

Extension hose.

















		Order Number	Max. working	NoIn size	Diame-	Puiss	Passistina	
		Order Number	pressure	Nozzle size	ter	Price	Description	L
Pipe cleaning hose, ID 6		1		I			1	
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Hose assembly TR pipe cleaning DN6 14MPa	4	6.110-048.0	140 bar				10 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose	5	6.110-049.0	140 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose, DN 6, 30 m	6	6.110-050.0	140 bar				30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning nozzle								
Dirt blaster pipe cleaning D21/040	7	4.765-001.0		40	21 mm		The forward-tilted rotating pencil jet removes the most	
Dirt blaster pipe cleaning D30/040	8	4.765-004.0		40	30 mm		stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient hand-ling.	
Pipe cleaning nozzle	9	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet	: [
	10	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	11	5.763-017.0		50	30 mm		30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	t
Rotating pipe cleaning nozzle	12	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	

[■] Included in delivery.

Available accessories.

Extension hose.





















								Т
		Order Number	Flow rate	Nozzle size	Diame- ter	Price	Description	
Hard Surface Cleaner FRV 30								
Add-on kit rubber lip	1	2.642-910.0					For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	
Extension hose 5 m	2	4.440-939.0					5m extension hose for FRV 30. Connection sleeve included.	
Add-on kit hose attachment	3	2.642-528.0					Suction cup for fixing the suction hose to smooth surfaces.	
Add-on kit dirt trap	4	2.642-532.0					Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
FRV 30	5	2.111-010.0					Surface cleaner with integrated waste water pick-up	
Hard surface cleaner FR 30								
FR 30 Surface Cleaner	6	2.111-011.0			300 mm		Up to 10 times greater area coverage compared with the conventional high pressure jet.	
Hard surface cleaner FR 30 ME								
FR 30 ME surface cleaner	7	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kit for FF	1							
Nozzle kit for surface cleaners (type-specific) 500 - 650 l/h	8	2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	
Machine-specific nozzle kits for F	RV							
Nozzle kit 040 - for FRV	9	2.642-431.0		40			Machine-specific nozzle kit Kärcher power nozzles and jet nozzle for FRV 30.	
Hard surface cleaner FRV 30 Me								
Extension hose FRV 30 Me and FRV 50 Me	10	4.441-040.0					5 m extension hose for FRV 30 Me. Includes connecting adapter.	
FRV 30 Me Surface Cleaner	11	2.111-012.0					Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	;

[■] Included in delivery.

Available accessories.

Extension hose.

















		I		1	ı	1	
		Order Number	Flow rate			Price	Description
Cup foam lance		ı			I.		
Cup foam lance Basic 2	1	4.112-054.0	700-800 l/h				For high-pressure cleaners with a flow rate of 700-800 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.
Cup foam lance Advanced 042	2	2.112-018.0					Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.
Tank grey only for replacement 1L	3	6.414-050.0					Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).
Inno Foam Set							
Inno foam kit with detergent injector	4	2.112-000.0					High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set							
Easy Foam Set with RM injector	5	2.112-010.0					HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set							
Nozzle kit 060 for Inno/Easy Set 600 - 700 l/h	6	2.111-018.0	600-700 l/h				Optimal adaptation to different machine outputs for economic use.
Foam nozzle mounting kit				1			
Foam nozzle kit	7	2.112-013.0					Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

[■] Included in delivery.

Available accessories.

Extension hose.



















		Order Number	Length		Price	Description
Automatic, self-winding hose reels						
Add-on kit hose reel plastics	1	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.
Add-on kit hose reel	2	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.
Hose reel, automatic, 20 m, pain- ted	3	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.
Hose reel, automatic, basalt grey- coated	4	6.392-105.0	20 m			Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.
Hose reel, automatic, 20 m, stain- less steel	5	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.
ABS hose reel stainless steel	6	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.
Add-on kit hose reel TR 40m	7	6.392-442.0	40 m			Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).
Swivel holder	8	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.
ABS wall fastening stainless steel	9	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.

[■] Included in delivery.

Available accessories.

Extension hose.









		Order Number	Nozzle size		Price	Description
Wet blasting attachment (without r	nozzle)			'		
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment					
Nozzle pack TR wet jet set 0040	3	2.112-019.0	40			Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0 4.115-006.0.
Boron carbide nozzle						
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

[■] Included in delivery.

Available accessories.

Extension hose.











Color counting		Order Number	Price	De- scripti- on	
Geka coupling With hose nozzle, R 1/2"	1	6.388-461.0		with hose liner	
With hose nozzle, R 3/4"	2	6.388-455.0		with hose liner	
With female thread, R 3/4"	3	6.388-473.0		with female thread	
Suction filter Water filter	4	6.414-956.0		Suitable	
				for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	
Suction filter with check valve	5	4.730-012.0		Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	

[■] Included in delivery.

Available accessories.

Extension hose.







		Order Number			Price	De- scripti- on	
Fine-mesh water filter							
Fine-mesh water filter with adapter	6	4.730-102.0				Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Water supply hose			1	1			
Water supply hose	7	4.440-038.0				NW 13 R1" / R 3/4", up to 30 °C	

[■] Included in delivery.

Available accessories.

Extension hose.





		Order Number			Price	De- scripti- on	
Backflow check valve		'	1	·			
Backflow preventer	8	2.641-374.0				To prevent deter-gent getting getting into the drinking water cycle in case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection	

[■] Included in delivery.

Available accessories.

Extension hose.











		Order Number	Flow rate		Price	Description	
Push-on washing brush							
Push-on washing brush	1	4.762-497.0				With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.	
Push-on wash brush, M 18 x 1.5	2	4.113-001.0				Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush							
Rotating wash brush for < 800 l/h machines, nylon bristles	3	4.113-004.0	500-800 l/h			The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60° C. (M 18×1.5 , replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	4	4.113-003.0	500-800 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 x 1.5 (replaceable brush insert).	

[■] Included in delivery.

Available accessories.

Extension hose.