



## HD 9/50 Ge Cage

This product uses up to 500 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.



### 1 Industrial spray gun

- Robust and durable: The new Kärcher industrial trigger gun was designed specially for heavy-duty use.

### 2 Speed regulation

- The speed is automatically reduced in standby mode. This protects the engine and saves energy.



## HD 9/50 Ge Cage

- Robust industrial gun
- Dry run protection (optional)
- Speed regulation

### Technical data

Order no.	1.367-506.0	
EAN code	4039784731035	
Working pressure	bar / MPa	150-500 / 15-50
Flow rate	l/h	500-900
Max. inlet temperature	°C	max. 60
Pump type	Maximum performance Kärcher crankshaft pump	
Drive	Honda GX 660 Petrol	
Motor rating	kW	16
Weight	kg	135
Dimensions (L × W × H)	mm	930 × 800 × 920

### Equipment

Electro start	■	
High-pressure hose	m	10 / Heavy duty
Spray gun	Industrial trigger gun	
Stainless steel lance	mm	700
Flat jet nozzle	■	
Safety valve	■	
Elapsed time counter	■	

■ Included in the scope of supply.

# HD 9/50 GE CAGE

## 1.367-506.0

**KÄRCHER**


		Order no.	Length				Price	Description	
<b>High-pressure hoses</b>									
Pressure hose	1	6.391-848.0						650 bar, M 22 x 1.5	■
	2	6.391-856.0						650 bar, M 22 x 1.5.	□
	3	6.391-857.0							□
	4	6.391-020.0						Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 640 bar working pressure.	□
	5	6.391-846.0						650 bar, M 22 x 1.5	□
	6	6.391-847.0						650 bar, M 22 x 1.5.	□
	7	6.391-019.0						Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 620 bar working pressure.	□
<b>Trigger guns</b>									
Kärcher industry gun	8	4.775-824.0						650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	■
<b>Spray lances</b>									
Spray lance	9	4.760-679.0						With nozzle holder.	■
	10	4.760-653.0							□
	11	4.760-675.0							□
	12	4.760-677.0							□
Spray lance extension	13	4.760-699.0						Spray lance extension 800 mm, 65 MPa.	□
<b>Power nozzles</b>									
Flat jet nozzle	14	5.765-163.0						15° flat jet nozzle 15028 for high-pressure cleaner HD 9/50. Suitable for working pressures of up to 500 bar and 900 l/h (petrol, 60 Hz).	■
Point jet nozzle	15	5.765-160.0						Point jet nozzle 0028 for high-pressure cleaner HD 9/50. Suitable for working pressures of up to 500 bar and 900 l/h (petrol, 60 Hz).	□
<b>Attachment kits</b>									
Attachment kit water shortage protection	16	2.641-923.0						For petrol engines.	□
ABS protection against water shortage	17	2.851-028.0						ABS steering rollers.	□
<b>Kupplungen und Verbinder</b>									
Coupling	18	4.403-004.0						For connecting and extending HP hoses. Connection 2 x M22 x 1.5. Brass with rubber protection.	□
Grease for stainless steel threaded joints	19	6.280-180.0						Grease for stainless steel screw connections.	□
<b>Single-jet rotary nozzles</b>									
Power rotary jet F8	20	6.415-915.0						500 bar, 1.05 mm, 900 l/h, M 20 x 1, stainless steel.	□
Power rotary jet repair kit F8	21	6.025-437.0						Repair kit for power rotary jet, order no. 6.415-915.0. Suitable for 500 bar pressure and 900 l/h water flow rate. Includes rotor, seat and O-ring (28 x 2).	□
Tool for changing rotor seat	22	6.025-233.0						For F3, F4, F1, F25.	□
<b>Screw nozzles F21</b>									
Dummy nozzle F21	23	6.025-237.0						F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	□
Round jet nozzle F21, Saphir	24	6.025-222.0						Screw-on F21 sapphire round jet nozzle with a diameter of 0.70 mm. Suitable for working pressures of up to 3,000 bar.	□

■ Included in the scope of supply. □ Available accessories.

# HD 9/50 GE CAGE

## 1.367-506.0

**KÄRCHER**


MISSING PICTURE:  
M:\print\9899828\_  
std\_1\_86584\_acc.  
tif

		Order no.	Length					Price	Description	
<b>Pipe cleaning</b>										
Foot valve for pipe cleaning	25	6.470-223.0							Foot valve for convenient and safe use of accessories for effective pipe cleaning.	<input type="checkbox"/>
Pipe cleaning nozzle, standard	26	5.763-093.0							Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning nozzle, Quattro	27	5.763-094.0							Quattro pipe cleaning nozzle (500/15) for pipe cleaning hoses with G1/4" threaded connection. The chisel point nozzle configuration is 3x backward and 1x forward.	<input type="checkbox"/>
Pipe cleaning nozzle, Rotor	28	5.763-095.0							Rotor pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning hose	29	6.392-401.0							Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4" nozzle.	<input type="checkbox"/>
	30	6.392-402.0							Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	<input type="checkbox"/>
	31	6.392-403.0							For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	<input type="checkbox"/>
<b>Surface cleaner</b>										
Surface Cleaner FRI 50 Me	32	2.643-577.0							Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	<input type="checkbox"/>
Nozzle package 015 FRI 50 Me	33	6.415-044.0							Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 015.	<input type="checkbox"/>
<b>Abrasive blaster</b>										
Required adapter for abrasive blasters	34	5.401-325.0							M 20 x 1 IG to 9/16" UNF AG.	<input type="checkbox"/>
Abrasive blaster	35	6.025-253.0							Abrasive spray head for wet sand blasting. Nozzle size: 3 x 0.6. Only includes spray head. Without hose and lance.	<input type="checkbox"/>
Replacement nozzle for abrasive blaster	36	6.025-346.0							Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	<input type="checkbox"/>
F98 nozzle for abrasive blaster	37	6.025-434.0							0.6 mm, 3 pcs.	<input type="checkbox"/>
Nozzle F98 for abrasive blaster	38	6.025-256.0							0.6 mm	<input type="checkbox"/>
Suction lance	39	6.025-258.0							For the suction of spray agents.	<input type="checkbox"/>
Abrasive material hose	40	6.025-308.0							Abrasive hose.	<input type="checkbox"/>
Mounting tool for nozzle set	41	6.025-257.0							For F98 nozzles.	<input type="checkbox"/>
Abrasive	42	6.025-309.0							25 kg, 0.5-1.00 mm, garnet sand.	<input type="checkbox"/>
	43	6.025-310.0							25 kg, 0.7-1.40 mm, garnet sand.	<input type="checkbox"/>
<b>Multi-jet rotary nozzles</b>										
Nozzle carrier head TD09	44	9.899-828.0							6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.