

TRADE LINE 390

Performance you can Trust

Advanced M-Class
filtration vacuum
for use on site or in
the workshop.



Numatic
INTERNATIONAL

TRADELINE 390



“Powerful, robust and easy to move around site, TradeLine does the job and does it well.”

Robbie Walker
EcoElectrix



“Pull handle makes getting TradeLine from van to site easy. Long cable and large rear wheels are ideal for moving it around on the job.”

Shane Scott
Loaring Development Ltd



Engineered to Last 20 Years

Proudly designed, engineered and built by Europe's No. 1, right here in the U.K.

No Lifting & Carrying

Large rear wheels and extending handle provide easy transit across uneven surfaces and up stairs.

High Efficiency

Patented AirFlo technology, triple layer bags and HEPA 13 filter deliver advanced filtration where it's needed most.

Huge Cleaning Reach

Huge 28 metre cleaning reach means TradeLine can be used far away from an electrical source, without the need to plug and unplug.

M-Class Compliant

Construction dust kills hundreds of tradesmen a year, prosecutions for non-compliance result in large fines. Take no chances and get the right TradeLine vacuum for the job.


What type of vacuum extractor do you need?

The most hazardous dusts can only be controlled by M-Class or H-Class machines. M-Class is the minimum legal requirement when working with construction dusts*.

Many sites will not permit you to use machines that do not conform to these standards. The Workplace Exposure Limit (WEL) for silica is 0.1 mg/m3.

Machine Type	Materials	Maximum Permeability	Maximum Allowable Concentration (MAC)
L-Class Low Risk	General dust, mixed dust, gypsum	≤ 1.0%	Dusts with MAC > 1 mg/m3
M-Class Medium Risk	Soft / hardwood, silica, masonry, paint, plastic, ceramic	< 0.1%	Dusts with MAC ≥ 0.1 mg/m3
H-Class High Risk	Asbestos	< 0.005%	Dusts with MAC < 0.1 mg/m3

For guidance only. Find out more at www.hse.gov.uk/construction



HEPA 13 Filtration

Long-life HEPA filter cartridge provides advanced filtration where it's needed most.



TriTex Filtration

Triple-layer TriTex filter optimises filtration, cleanliness and capacity.



HepaFlo Bags

High-efficiency, self-seal HepaFlo Filter Bags enable clean and safe emptying.



Made for Tough By Europe's No.1

Designed and built for work, and to work hard by Europe's No.1 commercial vacuum manufacturer.



TRADE LINE 390



“Powerful, robust and easy to move around site, TradeLine does the job and does it well.”

Robbie Walker
EcoElectrix



“Pull handle makes getting TradeLine from van to site easy. Long cable and large rear wheels are ideal for moving it around on the job.”

Shane Scott
Loaring Development Ltd

Engineered to Last 20 Years

Proudly designed, engineered and built by Europe's No.1, right here in the U.K.

No Lifting & Carrying

Large rear wheels and extending handle provide easy transit across uneven surfaces and up stairs.

High Efficiency

Patented AirFlo technology, triple layer bags and HEPA 13 filter deliver advanced filtration where it's needed most.

Huge Cleaning Reach

Huge 28 metre cleaning reach means TradeLine can be used far away from an electrical source, without the need to plug and unplug.

Wood, concrete, brick and mortar pick up

Power and performance wherever and whenever you need it.

When on site, you need a vacuum that not only conforms to HSE requirements, but a vacuum that is tough, durable and built to last.

You need TradeLine...



No lifting or carrying



Handy tool storage (optional)



Large, "site-ready" wheels for stairs, kerbs and uneven surfaces

2200W* Automatic Power Take-off

The highest available automatic power take-off on the market, TradeLine is ready for even the most powerful power tools.

*230v only. 110v - 1100W.

Dust Extraction

Combines a specialist extractor vacuum and big clean-up machine for use in the workshop and on site.

LOOK FOR M-CLASS.



IT'S THE LAW!

AS10 Kit 2.9m Conicle Hose (32mm), Stainless Steel Wand Set, 300mm MultiFlo Dry Brush Floor Tool and Adapter, FreeFlo Floor Tool.



Specifications

	Rated Motor Power (W)	Power	Airflow Motor only	Dry Capacity	Filter Type	Rating	Cleaning Range	Weight	Dimensions (mm) (W x L x H)	Power Outlet Socket
TEM390	620	230v AC /110v	48 L/sec	18 Litres	HEPA 13 TriTex	M	28m	14.3Kg	400x450x1010	2200W Max load 1100W (110v)
TEL390	620	230v AC /110v	48 L/sec	18 Litres	HEPA 13 TriTex	L	28m	10.8Kg	400x450x600	-

